

Your Global Automation Partner



# UHF RFID Demo Tools Read Me

Technical Support Document



# Contents

1	About These Instructions .....	5
1.1	Target groups.....	5
1.2	Explanation of symbols used .....	5
1.3	Other documents .....	5
1.4	Feedback about these instructions.....	5
1.5	Turck service.....	6
2	Commissioning .....	7
2.1	Supported hardware .....	7
2.2	Installing the software.....	8
3	Operation .....	12
3.1	Displaying the tag arrangement (Gate) .....	12
3.2	Identifying null spots and determining tag position (Tag Trace) .....	16
3.3	Assessing the readability of tags (Tag Population) .....	18
4	Turck Subsidiaries - Contact Information .....	20



# 1 About These Instructions

These instructions describe the use of the UHF Demo Tools software for the TBEN-...RFID... block modules and UHF readers. Read the instructions carefully prior to using the software. This will prevent the risk of personal injury and damage to property. Keep these instructions safe during the service life of the product. If the product is passed on, pass on these instructions as well.

## 1.1 Target groups

These instructions are aimed at qualified personal and must be carefully read by anyone mounting, commissioning, operating, maintaining, dismantling or disposing of the device.

## 1.2 Explanation of symbols used

The following symbols are used in these instructions:



### **DANGER**

DANGER indicates a dangerous situation with high risk of death or severe injury if not avoided.



### **WARNING**

WARNING indicates a dangerous situation with medium risk of death or severe injury if not avoided.



### **CAUTION**

CAUTION indicates a dangerous situation of medium risk which may result in minor or moderate injury if not avoided.



### **NOTICE**

NOTICE indicates a situation which may lead to property damage if not avoided.



### **NOTE**

NOTE indicates tips, recommendations and useful information on specific actions and facts. The notes simplify your work and help you to avoid additional work.



### **CALL TO ACTION**

This symbol denotes actions that the user must carry out.



### **RESULTS OF ACTION**

This symbol denotes relevant results of actions.

## 1.3 Other documents

Besides this document the following material can be found on the Internet at [www.turck.com](http://www.turck.com):

- Instructions for use
- Data sheet
- Approvals
- Configuration manual

## 1.4 Feedback about these instructions

We make every effort to ensure that these instructions are as informative and as clear as possible. If you have any suggestions for improving the design or if some information is missing in the document, please send your suggestions to [techdoc@turck.com](mailto:techdoc@turck.com).

## 1.5 Turck service

Turck supports you with your projects, from initial analysis to the commissioning of your application. The Turck product database under [www.turck.com](http://www.turck.com) contains software tools for programming, configuration or commissioning, data sheets and CAD files in numerous export formats.

The contact details of Turck subsidiaries worldwide can be found on p. [► 20].

## 2 Commissioning

### 2.1 Supported hardware

The UHF Demo Tools software is supported by the following devices:

RFID interface	Firmware
TBEN-S2-2RFID-4DXP	≥ 3.6.0.0
TBEN-L...-4RFID-8DXP	≥ 1.1.0.0
UHF readers	Firmware
TN-UHF-Q300-...-CDS	≥ 1.4.5.0
TN...-Q...L...-H1147 (connected to one of the above RFID interfaces)	≥ 1.45

## 2.2 Installing the software

The UHF Demo Tools software can be downloaded free of charge from [www.turck.com](http://www.turck.com).

- ▶ Download the software.
- ▶ Unpack the zip file.
- ▶ Click **UhfDemoTools-v1.1.22.0.exe**

Name	Type	Size
 <b>UhfDemoTools-v1.1.22.0.exe</b>	Application	2.385 KB

Fig. 1: Running the .exe file

- ▶ Double-click the Turck icon in the taskbar.



Fig. 2: Clicking the Turck icon

- ▶ Open the web server with a web browser or the Turck Service Tool.
- ▶ Click the **Refresh List** in the web server to find all compatible devices.
- ▶ Click **Open**.
- ▶ Alternatively: Enter the IP address of the device directly.




Fig. 3: Web server – clicking Refresh or entering an IP address

- ⇒ The device is displayed in the web server.

A login is required in order to edit settings via the web server. The default password is "password".



### NOTE

To ensure greater security, Turck recommends changing the password after the first login.

- ▶ Enter the password in the Login field on the start page of the web server.
- ▶ Click **Login**.

SELECT DEVICE
MAIN
UHF RFID CONFIG & DEMO
DOCUMENTATION

LOGIN

**TN-UHF-Q300-EU-CDS**

- Info
- Parameter
- Diagnosis
- Status
- Event log
- Ex- / Import
- Change Password

---

**LOCAL I/O**

- Parameter
- Diagnosis
- Input
- Output

**TN-UHF-Q300-EU-CDS - Gateway - Info**

Read/Write Head  
UHF RFID

**Device**

Station information				
Type	TN-UHF-Q300-EU-CDS			
Ident. no.	100000895			
Firmware revision	1.4.9.0			
Bootloader revision	1.0.1.0			
CODESYS Runtime version	3.5.14.10			
WEB revision	1.1.22.0			
Addressing mode	PGM-DHCP		?	
<b>Special device properties</b>				
Version code	UBPVYV		?	
Serial number	421528353		?	
Hardware version	1.0		?	

Fig. 4: Web server – login

- Change the password after the initial login.




Fig. 5: Web server – changing the password

- Click UHF RFID CONFIG & DEMO → GO ONLINE.




Fig. 6: Web server – Go online

- Click **Application** at the bottom left of the screen in the navigation bar.
- ⇒ The **Tag Population**, **Tag Trace** and **Gate** functions are displayed and can be selected.




Fig. 7: Web server – RFID Application

### 3 Operation

#### 3.1 Displaying the tag arrangement (Gate)

Example: gate application in logistics

Several tagged goods are read and identified by an UHF reader as they pass through an RFID gate. A feasibility study examines whether the RFID tags are identified reliably or whether environmental conditions or physical factors have a negative effect on the performance of UHF reader.



Fig. 8: Gate application in logistics: All tags on the pallet are identified as they pass through the gate



Fig. 9: Example: typical arrangement of packaging on a pallet

## Using the gate function

The **Gate** function enables the physical arrangement of several tags in multi-tag applications to be transferred to a 2D matrix where they are displayed. Each EPC is provided with a separate field in the matrix. The field of the EPC turns green if a read operation is successful. In this way, unread tags can be identified.

**Gate**

Columns:  Rows:  DRAW GATE ?

☐ Fill gate with EPCs ?

SORT BY ROW
SORT BY COLUMN
DELETE EPC
?

☐ Change length of EPCs ?

**Gate with EPC positions**

EPCs can be arranged with drag and drop

Empty	Empty	Empty
Empty	Empty	Empty
Empty	Empty	Empty

☐ Start/Stop Inventory Stop after [ms]  ?

Fig. 10: User interface of the Gate function

### Creating a matrix:

- ▶ Enter the required number of **Columns** and **Rows**.
- ▶ Click **DRAW GATE**.
- ⇒ The 2D matrix is created.

The screenshot shows the 'Gate' configuration window. At the top, there are input fields for 'Columns: 3' and 'Rows: 3', followed by a yellow 'DRAW GATE' button. Below this is a checkbox 'Fill gate with EPCs' which is currently unchecked. Further down are three buttons: 'SORT BY ROW', 'SORT BY COLUMN', and 'DELETE EPC'. Below these is another checkbox 'Change length of EPCs' which is also unchecked. The main section is titled 'Gate with EPC positions' and includes the text 'EPCs can be arranged with drag and drop'. Below this text is a 3x3 matrix table with all cells containing the word 'Empty'. At the bottom, there is a checkbox 'Start/Stop Inventory' and a text input field 'Stop after [ms] 0'. A red rectangle highlights the 'Columns', 'Rows', 'DRAW GATE', 'Fill gate with EPCs', and the 3x3 matrix area.

**Gate**

Columns: 3 Rows: 3 **DRAW GATE** ?

☐ Fill gate with EPCs ?

**SORT BY ROW** **SORT BY COLUMN** **DELETE EPC** ?

☐ Change length of EPCs ?

**Gate with EPC positions**  
EPCs can be arranged with drag and drop

Empty	Empty	Empty
Empty	Empty	Empty
Empty	Empty	Empty

☐ Start/Stop Inventory Stop after [ms] 0 ?

Fig. 11: Creating a matrix

### Reading and sorting EPCs:

- ▶ Click **Fill gate with EPCs**.
- ⇒ The RF field is activated and all identified EPCs are inserted in the empty fields.
- ▶ Sorting EPCs: by row (**SORT BY ROW**), by column (**SORT BY COLUMN**) or manually by drag and drop
- ▶ Deleting an EPC: Select the EPC and click **DELETE EPC**.

This screenshot is identical to the one in Figure 11, showing the 'Gate' configuration window with the 3x3 matrix. A red rectangle highlights the 'Fill gate with EPCs' checkbox and the 'SORT BY ROW', 'SORT BY COLUMN', and 'DELETE EPC' buttons, indicating the next steps in the process.

**Gate**

Columns: 3 Rows: 3 **DRAW GATE** ?

☐ Fill gate with EPCs ?

**SORT BY ROW** **SORT BY COLUMN** **DELETE EPC** ?

☐ Change length of EPCs ?

**Gate with EPC positions**  
EPCs can be arranged with drag and drop

Empty	Empty	Empty
Empty	Empty	Empty
Empty	Empty	Empty

☐ Start/Stop Inventory Stop after [ms] 0 ?

Fig. 12: Adding, sorting and deleting EPCs

### Starting and stopping the read operation:

- ▶ Click **Start/Stop Inventory**.
- ⇒ The UHF reader is switched on and the Inventory operation is started.
- ⇒ If the UHF reader identifies an EPC, the corresponding field in the matrix is green. The read operation was successful.

**Gate**

Columns:  Rows:  DRAW GATE ?

☐ Fill gate with EPCs ?

SORT BY ROW SORT BY COLUMN DELETE EPC ?

☐ Change length of EPCs ?

**Gate with EPC positions**  
EPCs can be arranged with drag and drop

0000 0000 1234 5abc de10 2310 [26]	e2c0 6892 0000 003a 1e33 d80c [14]	e2c0 6892 0000 003a 1e33 d80e [8]
0000 0000 1234 5abc de10 2311 [26]	0000 0000 1234 5abc de10 2308 [26]	0000 0000 1234 5abc de10 2309 [26]
0000 0000 1234 5abc de10 2313 [26]	0000 0000 1234 5abc de10 2314 [26]	0000 0000 1234 5abc de10 2312 [26]

☐ Start/Stop Inventory Stop after [ms]  ?

-40

Fig. 13: Read operation successful

- ▶ Click **Start/Stop Inventory**

or

- ▶ In the **Stop after [ms]** enter the time after which the operation is stopped automatically.
- ⇒ The read operation is stopped and the RF field is switched off.

**Gate**

Columns:  Rows:  DRAW GATE ?

☐ Fill gate with EPCs ?

SORT BY ROW SORT BY COLUMN DELETE EPC ?

☐ Change length of EPCs ?

**Gate with EPC positions**  
EPCs can be arranged with drag and drop

0000 0000 1234 5abc de10 2310 [26]	e2c0 6892 0000 003a 1e33 d80c [14]	e2c0 6892 0000 003a 1e33 d80e [8]
0000 0000 1234 5abc de10 2311 [26]	0000 0000 1234 5abc de10 2308 [26]	0000 0000 1234 5abc de10 2309 [26]
0000 0000 1234 5abc de10 2313 [26]	0000 0000 1234 5abc de10 2314 [26]	0000 0000 1234 5abc de10 2312 [26]

Start/Stop Inventory Stop after [ms]  ?

-40

Fig. 14: Start/stop Inventory

### 3.2 Identifying null spots and determining tag position (Tag Trace)

Example: guided single-tag application (dynamic)

The tagged goods on a conveyor pass read points and are identified by a UHF reader. Environmental factors can cause null spots in the read operation, thus preventing the reading of tags.



Fig. 15: Example: Identification of individual products on a conveyor belt

## Using the Tag Trace function

The **Tag Trace** function enables the quality of read operations on the air interface to be determined. The received RSSI values (i.e. the received signal strength) of a tag are displayed graphically over time in a plot. Using the graph of signal strength over time, the user can determine whether the tag is reliably detected and whether the ideal time is possibly further left or right of the current position of the UHF reader. Up to four measurements can be recorded and displayed per tag. The plots are dimmed successively in stages. The lighter the plot the older the measurement.

- Click **Start/Stop Inventory** to start or stop the read operation.
- ⇒ The received RSSI values over time are displayed as a graph.




Fig. 16: RSSI signal strength of a tag over time

### 3.3 Assessing the readability of tags (Tag Population)

The constitution of the mounting surface and the immediate environment of the tag may so severely reduce the readability of a tag that detection is no longer possible even with a high output power. The **Tag Population** function makes it possible to assess the readability of a tag at a specific position and the minimum output power of the UHF reader required to read each tag.

- ▶ Enter the output powers of the UHF reader to be tested in the **Start power** and **End power** fields (here: **5** and **15** dBm).
- ▶ In the **Interval** drop-down list select how long the UHF reader searches for tags at each power value (here: **1000 ms**).
- ▶ Click **Start**.
- ⇒ The UHF reader increases the power in stages (power sweep) and displays the number of tags read for each output power.
- ⇒ The software displays the trace of recorded values with a gray progress bar.




Fig. 17: Number of read tags per output power

The following information is displayed in a table:

- Minimum power required by the UHF reader to detect the tag
- RSSI over power: Change in signal strength (RSSI) in relation to increasing output power


	EPC / Antenna (7)	min. required Power [dBm]	Count (81)
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2308 RHCP	11	3
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2309 RHCP	10	9
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2310 RHCP	6	19
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2311 RHCP	7	20
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2312 RHCP	8	16
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2313 RHCP	11	3
<input type="checkbox"/> 	0000 0000 1234 5abc de10 2314 RHCP	5	11

Fig. 18: List of read tags

## 4 Turck Subsidiaries - Contact Information

<b>Germany</b>	Hans Turck GmbH & Co. KG Witzlebenstraße 7, 45472 Mülheim an der Ruhr <a href="http://www.turck.de">www.turck.de</a>
<b>Australia</b>	Turck Australia Pty Ltd Building 4, 19-25 Duerdin Street, Notting Hill, 3168 Victoria <a href="http://www.turck.com.au">www.turck.com.au</a>
<b>Belgium</b>	TURCK MULTIPROX Lion d'Orweg 12, B-9300 Aalst <a href="http://www.multiprox.be">www.multiprox.be</a>
<b>Brazil</b>	Turck do Brasil Automação Ltda. Rua Anjo Custódio Nr. 42, Jardim Anália Franco, CEP 03358-040 São Paulo <a href="http://www.turck.com.br">www.turck.com.br</a>
<b>China</b>	Turck (Tianjin) Sensor Co. Ltd. 18,4th Xinghuazhi Road, Xiqing Economic Development Area, 300381 Tianjin <a href="http://www.turck.com.cn">www.turck.com.cn</a>
<b>France</b>	TURCK BANNER S.A.S. 11 rue de Courtalin Bat C, Magny Le Hongre, F-77703 MARNE LA VALLEE Cedex 4 <a href="http://www.turckbanner.fr">www.turckbanner.fr</a>
<b>Great Britain</b>	TURCK BANNER LIMITED Blenheim House, Hurricane Way, GB-SS11 8YT Wickford, Essex <a href="http://www.turckbanner.co.uk">www.turckbanner.co.uk</a>
<b>India</b>	TURCK India Automation Pvt. Ltd. 401-403 Aurum Avenue, Survey. No 109 /4, Near Cummins Complex, Baner-Balewadi Link Rd., 411045 Pune - Maharashtra <a href="http://www.turck.co.in">www.turck.co.in</a>
<b>Italy</b>	TURCK BANNER S.R.L. Via San Domenico 5, IT-20008 Bareggio (MI) <a href="http://www.turckbanner.it">www.turckbanner.it</a>
<b>Japan</b>	TURCK Japan Corporation Syuuhou Bldg. 6F, 2-13-12, Kanda-Sudacho, Chiyoda-ku, 101-0041 Tokyo <a href="http://www.turck.jp">www.turck.jp</a>
<b>Canada</b>	Turck Canada Inc. 140 Duffield Drive, CDN-Markham, Ontario L6G 1B5 <a href="http://www.turck.ca">www.turck.ca</a>
<b>Korea</b>	Turck Korea Co, Ltd. B-509 Gwangmyeong Technopark, 60 Haan-ro, Gwangmyeong-si, 14322 Gyeonggi-Do <a href="http://www.turck.kr">www.turck.kr</a>
<b>Malaysia</b>	Turck Banner Malaysia Sdn Bhd Unit A-23A-08, Tower A, Pinnacle Petaling Jaya, Jalan Utara C, 46200 Petaling Jaya Selangor <a href="http://www.turckbanner.my">www.turckbanner.my</a>

<b>Mexico</b>	Turck Comercial, S. de RL de CV Blvd. Campestre No. 100, Parque Industrial SERVER, C.P. 25350 Arteaga, Coahuila <a href="http://www.turck.com.mx">www.turck.com.mx</a>
<b>Netherlands</b>	Turck B. V. Postbus 297, NL-8000 AG Zwolle <a href="http://www.turck.nl">www.turck.nl</a>
<b>Austria</b>	Turck GmbH Graumanngasse 7/A5-1, A-1150 Wien <a href="http://www.turck.at">www.turck.at</a>
<b>Poland</b>	TURCK sp.z.o.o. Wroclawska 115, PL-45-836 Opole <a href="http://www.turck.pl">www.turck.pl</a>
<b>Romania</b>	Turck Automation Romania SRL Str. Siriului nr. 6-8, Sector 1, RO-014354 Bucuresti <a href="http://www.turck.ro">www.turck.ro</a>
<b>Russian Federation</b>	TURCK RUS OOO 2-nd Pryadilnaya Street, 1, 105037 Moscow <a href="http://www.turck.ru">www.turck.ru</a>
<b>Sweden</b>	Turck Sweden Office Fabriksstråket 9, 433 76 Jonsered <a href="http://www.turck.se">www.turck.se</a>
<b>Singapore</b>	TURCK BANNER Singapore Pte. Ltd. 25 International Business Park, #04-75/77 (West Wing) German Centre, 609916 Singapore <a href="http://www.turckbanner.sg">www.turckbanner.sg</a>
<b>South Africa</b>	Turck Banner (Pty) Ltd Boeing Road East, Bedfordview, ZA-2007 Johannesburg <a href="http://www.turckbanner.co.za">www.turckbanner.co.za</a>
<b>Czech Republic</b>	TURCK s.r.o. Na Brne 2065, CZ-500 06 Hradec Králové <a href="http://www.turck.cz">www.turck.cz</a>
<b>Turkey</b>	Turck Otomasyon Ticaret Limited Sirketi Inönü mah. Kayisdagi c., Yesil Konak Evleri No: 178, A Blok D:4, 34755 Kadiköy/ Istanbul <a href="http://www.turck.com.tr">www.turck.com.tr</a>
<b>Hungary</b>	TURCK Hungary kft. Árpád fejedelem útja 26-28., Óbuda Gate, 2. em., H-1023 Budapest <a href="http://www.turck.hu">www.turck.hu</a>
<b>USA</b>	Turck Inc. 3000 Campus Drive, USA-MN 55441 Minneapolis <a href="http://www.turck.us">www.turck.us</a>

# TURCK

Over 30 subsidiaries and over  
60 representations worldwide!

100024995 | 2021/04



[www.turck.com](http://www.turck.com)